





YUXIN PRODUCT PRICE & SPECIFICATION

Model	PHOTO	Voltage	Power input	Input Power of Compressor/Chilling Wattage	Water Production Capacity	Heating Wattage	Temperature of Cold Water	Temperature of Hot Water	Net Weight	Gross Weight	Inlet Pressure	Storage Capacity of bottom tank	Storage Capacity of top tank
EA-60		A.C.220V/50HZ A.C.110V/60HZ	1600W	1000W	60L/Day	500W	4-10°C	75-95°C	90kg	110kg	0.1-0.6Mpa	4L	37.9L
					30°C 80%								
EA-200		A.C.380V/50HZ A.C.380V/60HZ	3.8KW	2.6KW/125W	200L/Day 30°C 80%	500W	4-10°C	75-95°C	260kg	290kg	0.1-0.6Mpa	28.4L	60.5L
制衣： 左军						审核：					批准：		

日期



YUXIN PRODUCT PRICE & SPECIFICATION

Storage Capacity of cold tank	Storage Capacity of hot tank	Total Storage Capacity	Compressor	Gas	Amount of gas	Working Conditions	Machine Size(CM)	Carton Packing Size(CM)	Plywood packing size	Loading Quantity		Noise Level	Defrost Method	Phase Protection of Compressor
										20ft(units)	0ft HQ(units)			
2.8L	2.7L	47.4L	HITACHI	R407c R134a	750g	15°C-40°C (35%RH-95%RH)	59*59*111	60*63*115	65*68*120	45-50	114	<75DB	COMPUTERIZE	Phase-sequence Protection / Delay Protection / Hi & Low Pressure Protection / Overheat & Overload Protection
10.2L	6.85L	90L	HITACHI	R407c	2.2kg	15°C-40°C (35%RH-95%RH)	80*70*170	81*74*174	86*79*179	35-40	100-110	<79DB	COMPUTERIZE	Phase-sequence Protection / Delay Protection / Hi & Low Pressure Protection / Overheat & Overload Protection
期 : 2014.06														